



The 280 and 290 Series, 1" Impactool delivers exceptional power and rugged durability in a convenient, easy-to-use package.

With 2 169 Nm (1 600 ft-lb) of maximum torque, these are perfect tools for the most demanding applications, such as truck and bus service, construction and agricultural equipment maintenance, tire changing, as well as the MRO market.

- ◆ 2 169 Nm (1 600 ft-lb) of maximum torque
- ◆ JumboHammer impact mechanism for power and durability

Specifications at 6.2 bar (90 PSI)

Part number	290-EU
Ordering number	01343177
Drive size (square)	1 in
Also available with 6" / 152 mm extended anvil:	290-6-EU

PERFORMANCE

Working torque	150 - 1 000 ft-lb / 203 - 1 356 Nm
Maximum torque	1 600 ft-lb / 2 169 Nm
Recommended fastener size	1.1/4 in / M32
Maximum free speed	6 000 rpm
Impacts per minute	800

AIR SYSTEM

Air inlet (NPTF)	1/2 in
Minimum hose size	3/4 in / 19 mm
Average air consumption	10 cfm / 283 l/min
Air consumption at load	60 cfm / 1 699 l/min

NOISE & VIBRATIONS

Sound pressure / power	104.6 / 117.6 dB(A)
Vibration level (ISO8662)	12.2 m/s²

WEIGHT & DIMENSIONS

Tool weight	21.9 lb / 9.93 kg
Tool length	9.75 in / 248 mm
Shipping weight	25.3 lb / 11.5 kg
Shipping dimensions (l x w x h)	320 x 380 x 160 mm
UPC/EAN Code	6 63023 00385 6
Origin	Assembled in USA

